BenQ RP6503(9H.F82TK.DE5) BenQ RP6503 - 65"Diagonal Class Pro Series LED-backlit LCD display - interactive - with touchscreen (multi touch) - 4K UHD (2160p) 3840 x 2160 - direct-lit LED



Encourage active participation in class while protecting student and teacher health with BenQ's best interactive display for education.

Key Selling Points

Germ-resistant screen,pen,and remote Built-in air ionizer for clean air 2 x 16 W speakers with subwoofer for immersive sound One-tap NFC login to instantly load lesson materials Interactive teaching tools for more hands-on lessons

Product Features

Maximum eye protection

The RP03 is the first and only interactive display to meet Eyesafe standards,offering the highest level of protection available for the eyes. By minimizing high-energy blue light emission, the RP03 reduces eye strain while maintaining vivid, true-to-life colors.

Discover new ways to teach

Teach with confidence knowing all the classroom tools you need to give great lessons are always a tap away.

A more flexible teaching experience

Everything you need to give immersive lessons is already built in. Teach from anywhere in the classroom without external devices or additional software.

Captivate your class

Encourage active participation at every lesson with a wide variety of teaching tools that make classes fun. Whether you're teaching in person or holding a hybrid class,keep your students engaged and boost their learning retention.

Engagement on the display

Get a smooth and intuitive writing experience that allows multiple students to interact with the display at the same time for group work and competitions. With the EZWrite 6 whiteboard, you can make use of fun classroom tools to give more engaging lessons.

Immersive audio and visuals

Experience unmatched audiovisuals on the first and only interactive display with rich Dolby Digital Plus sound on the built-in 2 x 16 speakers with subwoofer and crystal-clear 4K UHD images.

Main Specifications

| Product Description | BenQ RP6503 Pro Series - 65"LED-backlit LCD display - 4K - for interactive communication |
|--------------------------|--|
| Product Type | LED-backlit LCD flat panel display with touchscreen (multi touch) |
| Diagonal Class | 65" |
| Commercial Use | Yes - interactive |
| Resolution | 3840 x 2160 |
| Display Format | 4K UHD (2160p) |
| Video Interface | HDMI |
| HDMI Ports Qty | 3 ports |
| PC Interface | VGA (HD-15),DisplayPort |
| Technology | IPS |
| LCD Backlight Technology | Direct-lit LED |
| Image Aspect Ratio | 16:9 |

| Picture Enhancements | 72% Colour Gamut NTSC |
|-------------------------------|---------------------------------|
| Speaker System | 2 speakers, subwoofer |
| Storage Capacity | 64 GB |
| USB | Yes |
| Included Accessories | Remote control,2 styluses |
| Voltage | AC 100-240 V (50/60 Hz) |
| Energy Class | Class G |
| Power Consumption Operational | 80.4 Watt |
| Power Consumption Stand by | 0.5 Watt |
| Dimensions (WxDxH) | 148.93 cm x 12.15 cm x 93.43 cm |
| Weight | 43 kg |

Extended Specification

General

| Product Type | LED-backlit LCD flat panel display |
|---------------------------------|---|
| Energy Class | Class G |
| Power Consumption (Max) | 411.2 Watt |
| Power Consumption Operational | 80.4 Watt |
| Power Consumption SDR (On mode) | 191 kWh/1000h |
| Diagonal Class | 65" |
| Commercial Use | Yes - interactive |
| Combined With | Touchscreen (multi touch) |
| Series | Pro Series |
| TV Tuner Presence | No |
| Sensors | Ambient light sensor (ALS),temperature sensor,motion sensor,NFC sensor,air quality sensor,humidity sensor |
| Video Interface | HDMI |
| HDMI Ports Qty | 3 ports |
| PC Interface | VGA (HD-15),DisplayPort |
| Modes | Landscape mode |
| Picture Enhancements | 72% Colour Gamut NTSC |
| Protection | Tempered glass protection,germ-resistant |
| Width | 148.93 cm |
| Depth | 12.15 cm |
| Height | 93.43 cm |
| Weight | 43 kg |
| | |

Display

| LCD Display Technology | IPS |
|--------------------------|----------------|
| Pixel Pitch | 0.37 mm |
| Resolution | 3840 x 2160 |
| Display Format | 4K UHD (2160p) |
| Image Aspect Ratio | 16:9 |
| LCD Backlight Technology | Direct-lit LED |

| Coating | Anti-glare,9H Hard |
|----------------------------|--|
| Image Contrast Ratio | 1200:1 |
| Dynamic Contrast Ratio | 30000:1 |
| Brightness | 400 cd/m ² |
| Viewing Angle | 178 degrees |
| Viewing Angle (Vertical) | 178 degrees |
| Touchpoints Qty | 40 |
| Response Time | 8 ms |
| Backlight Life | 50,000 hour(s) |
| Operation Hours / Days | 18 / 7 |
| Features | Infrared touch technology,Low Blue Light Technology,EZWrite Software,Flicker free technology,18/7 operation time,10-bit support,OPS Slot |
| Stands & Mounts | |
| Wall Mount Included | Yes |
| Flat Panel Mount Interface | 600 x 400 mm |
| VESA Compatibility | Yes |
| Media Player | |
| USB Port | Yes |
| | |

| USB Port | Yes |
|------------------|---|
| Configuration | 4 x ARM Cortex-A73 + 4 x ARM Cortex-A53 - 8 GB - 64 GB - Mali G52 MP8 |
| Operating System | Android OS 11 |

Remote Control

| Туре | Remote control |
|----------------------|---|
| Audio System | |
| Digital Audio Format | Dolby Digital Plus output |
| Speaker System | 2 speakers,subwoofer |
| Features | Built-in 8-array microphone |
| Speakers | 2 x main channel speaker - 16 Watt 1 x subwoofer - 16 Watt |

Connections

| Connector | Туре |
|-----------|------|
|-----------|------|

3 x touch VGA input 3 x HDMI input DisplayPort Microphone 2 x USB 2.0 5 x USB 3.2 Gen 1 2 x USB 3.0 RS-232 2 x LAN HDMI output Audio line-out SPDIF output

Miscellaneous

| Included Accessories | 2 styluses |
|----------------------|---|
| Cables Included | VGA cable - 3 m HDMI cable - 3 m USB touch cable - 3 m USB-C cable - 1.5 m |

Power

| Power Device | Power supply |
|----------------------------|-------------------------|
| Input Voltage | AC 100-240 V (50/60 Hz) |
| Power Consumption Stand by | 0.5 Watt |

Dimensions & Weight (Shipping)

| Width (Shipping) | 166 cm |
|-------------------|----------|
| Depth (Shipping) | 22 cm |
| Height (Shipping) | 104.5 cm |
| Weight (Shipping) | 56 kg |

Environmental Parameters

| Min Operating Temperature | 0°C |
|---------------------------|------------------------------|
| Max Operating Temperature | 40 °C |
| Humidity Range Operating | 20 - 80% RH (non-condensing) |

What's in the box

BenQ RP6503 Remote control VGA cable - 3 m HDMI cable - 3 m USB touch cable - 3 m USB-C cable - 1.5 m Wall mount 2 styluses

Product data is provided by CNET, we do not warrant the accuracy and completeness of the material contained in this data sheet